


State of Oregon
Oregon Department of Geology and Mineral Industries
Brad Avy, State Geologist

BASE FLOOD ELEVATION DETERMINATION BF-16-01

BASE FLOOD ELEVATION DETERMINATION FOR LOWER REACH OF GATE CREEK NEAR VIDA, LANE COUNTY, OREGON

by Jed T. Roberts¹ and Matt C. Williams¹



2016

¹Oregon Department of Geology and Mineral Industries, 800 NE Oregon Street, Suite 965, Portland, OR 97232

DISCLAIMER

The Oregon Department of Geology and Mineral Industries is not liable for any claimed damage from the use of this information. The Federal Emergency Management Agency may, at any time in the future, revise the Base Flood Elevations for this study area. This study and Base Flood Elevation determination does not supersede any existing or future detailed analyses or determination performed by a licensed professional engineer. This analysis and mapping does not necessarily identify all areas subject to flooding, particularly from local drainage sources of small size.

Oregon Department of Geology and Mineral Industries Base Flood Elevation Determination BF-16-01
Published in conformance with ORS 516.030

This report was prepared by the Oregon Department of Geology and Mineral Industries for AKS Engineering and Forestry, LLC, in fulfillment of the Base Flood Elevation Determination Service Agreement made effective February 18, 2016.

For additional information:
Administrative Offices
800 NE Oregon Street #28, Suite 965
Portland, OR 97232
Telephone (971) 673-1555
Fax (971) 673-1562
<http://www.oregongeology.org>
<http://www.oregon.gov/DOGAMI/>

TABLE OF CONTENTS

Study Background.....1

Physical Setting.....3

Hydrologic Analysis Methods4

Hydraulic Analysis Methods6

Summary of Results.....7

References.....8

Appendix A: Map of Hydraulic Analysis Results9

Appendix B: Hydraulic Analysis Data Package10

LIST OF FIGURES

Figure 1. Zone A Special Flood Hazard Area (FEMA, 1999)2

Figure 2. Location of study reach3

Figure 3. Discharge locations.....5

Figure 4. Location of cross-sections used for hydraulic analysis.....7

LIST OF TABLES

Table 1. Summary of 100-year flood discharges.....5

Table 2. Summary of 100-Year flood elevations7

STUDY BACKGROUND

This study was conducted under a Base Flood Elevation Determination Service agreement dated February 18, 2016, between the Oregon Department of Geology and Mineral Industries (DOGAMI) and AKS Engineering and Forestry, LLC. The purpose of this study was to develop 1% annual chance (100-year) water surface elevations, also known as Base Flood Elevations (BFEs), for the lower reach of Gate Creek in Lane County, Oregon, near the unincorporated community of Vida.


BFEs are determined primarily for administration of the National Flood Insurance Program (NFIP). The Federal Emergency Management Agency (FEMA) oversees the NFIP and issues Flood Insurance Rate Maps (FIRMs) that depict Special Flood Hazard Areas (SFHAs) within which flood insurance for structures is typically required. SFHAs are mapped by *detailed* or *approximate* methods:

- *Detailed analyses* are performed for streams in urban or suburban settings, and SFHAs mapped with this approach are designated as Zone AE, Zone AO, or Zone AH. The analyses incorporate field survey and flood frequency data into a hydraulic model. The resulting BFEs are mapped onto best available topographic data.
- *Approximate analyses* are performed for streams in rural areas, and SFHAs mapped with this approach are designated as Zone A. Unlike detailed analyses, the approximate analysis does not produce BFEs. Instead, this latter method has historically involved engineering judgment of hydraulics and hydrology to map SFHAs onto U.S. Geological Survey (USGS) topographic sheets.

The approximate analysis approach was used to map SFHAs that are shown on the currently effective FIRM for Gate Creek (Figure 1).

DOGAMI has partnered with FEMA through its Cooperating Technical Partner program to improve FIRMs by introducing high-resolution lidar (light detection and ranging) topographic data. As part of this effort DOGAMI has developed a FEMA-approved computer model-based approach to produce BFEs using lidar in areas designated approximate, enabling the Zone A SFHAs to be revised and updated. This same approach was applied for the current study to produce BFEs in an area where FEMA has not yet funded a lidar-based FIRM revision.

Figure 1. Zone A Special Flood Hazard Area (FEMA, 1999).




PHYSICAL SETTING

Gate Creek drains a 48.1-square-mile watershed within the southeastern Willamette River Basin along the western slope of the Cascade Range. It is a tributary to the McKenzie River with the confluence upstream of river mile 41 (Figure 2). The watershed is characterized by steep forested uplands typical of the western Cascade Range. Timber harvests have moderately altered the watershed. Mean annual precipitation in the watershed ranges from approximately 60 to 80 inches per year. Flows do not appear to be regulated by dams or other hydraulic structures.

Gate Creek appears to have been relatively stable in its planform configuration throughout recent history. The channel is moderately confined by bedrock along most of the reach, with valley widths of approximately 500 feet. In the middle of the reach the valley expands to 1,500 feet, where evidence of downcutting is seen in a three-tiered terrace succession, clearly visible from lidar data collected in 2009 (DOGAMI, 2010).

Figure 2. Location of study reach.



HYDROLOGIC ANALYSIS METHODS

Two discharge locations were identified for this study. Locations were selected at the downstream terminus of the study reach and upstream based on a minimum drainage area reduction of 1 square mile (Figure 3).

The 100-year peak discharges were calculated using a regional regression equation developed by the Oregon Water Resource Department (OWRD) and the USGS (Cooper, 2005). OWRD and USGS divided western Oregon into three hydrologic regions with separate regression equations. The watershed upstream of the discharge locations fall completely within Region 2B. For these ungaged locations the 100-year peak discharge is given by the equation:

$$Q_{100} = 31.85 \text{ Area}^{0.9114} \text{ Slope}^{0.4501} I_{24-2}^{0.6252}$$

where

Q_{100} = the 100-year (1% annual chance) peak discharge, in cubic feet per second,

$Area$ = the drainage area of the watershed, in square miles,

$Slope$ = the mean watershed slope, in degrees, and

I_{24-2} = the 2-year (50% annual chance) 24-hour precipitation intensity, in inches.

Basin characteristics were determined using the USGS StreamStats for Oregon web tool (USGS, <https://water.usgs.gov/osw/streamstats/>, accessed 2015). The resulting 100-year peak discharges are listed in Table 1.

Figure 3. Discharge locations.




Table 1. Summary of 100-year flood discharges.

Discharge Location	Drainage Area (sq. mi.)	Mean Watershed Slope (deg.)	2-year 24-hour Precipitation Intensity (in.)	100-Year Peak Discharge (cfs)
Discharge Location #1	48.1	21.7	2.56	7,820
Discharge Location #2	46.6	22.0	2.57	7,660


HYDRAULIC ANALYSIS METHODS

To produce simulated water surface elevations of the 100-year peak discharge, a steady flow hydraulic model was developed by using the Hydrologic Engineering Center River Analysis System (HEC-RAS 4.1) produced by the U.S. Army Corps of Engineers (Brunner, 2010). Geometric input data were developed using the Esri ArcGIS® for Desktop Advanced 10.2.2 software package, the Esri 3D Analyst® and Spatial Analyst® extensions, and the HEC-GeoRAS 10.2 add-on produced by USACE (Ackerman, 2011).

Geometric data layers, including stream centerline, flowpaths, bank stations, and cross-sections, were digitized from a hillshade raster derived from a 3-foot resolution lidar digital elevation model (DEM). The lidar DEM was derived from ground classified points with an average density of 0.13 per square foot. The vertical accuracy for the lidar acquisition area is ± 0.26 feet on flat surfaces. Lidar acquisition for the study area took place on May 31, 2009 (DOGAMI, 2010).

Twenty-six cross-sections were placed along the study reach, perpendicular to the stream centerline (Figure 4). The downstream reach boundary condition was defined as known water surface elevations from BFEs published by FEMA (1999).

Manning's roughness coefficients were determined for the study area overbank areas using the 2011 National Land Cover Dataset (Jin and others, 2013). Land cover types were assigned a coefficient from land descriptions provided by Chow (1959). Overbank coefficients were found to range from 0.03 to 0.1 throughout the study area. Channel coefficients were determined by inspecting orthoimagery and are fairly consistent, ranging from 0.05 in the upper, more rugged reach, to 0.04 in the lower reach.

Figure 4. Location of cross-sections used for hydraulic analysis.

SUMMARY OF RESULTS

The results of hydraulic modeling show that BFEs range from 767.4 ft (NAVD88) at the downstream terminus of the study reach to 890.2 ft (NAVD88) at the upstream terminus. Table 2 shows BFEs at cross-sections selected approximately every river mile (Appendix A) throughout the study reach.

Table 2. Summary of 100-Year flood elevations.

Reference Cross-Section ¹	Location Description	BFE (ft. NAVD88 ²)
GC-1	mouth of Gate Creek	767.4
GC-2	1,200 feet upstream of the McKenzie Highway (State Route 126) bridge	789.9
GC-3	4,200 feet upstream of the McKenzie Highway (State Route 126) bridge	812.4
GC-4	5,500 feet downstream of confluence with South Fork Gate Creek	845.6
GC-5	2,200 feet downstream of confluence with South Fork Gate Creek	874.0
GC-6	just downstream of confluence with South Fork Gate Creek	890.2

¹See Appendix A for map of reference cross-sections.

²North American Vertical Datum of 1988.

REFERENCES

- Ackerman, C. T., 2011, HEC-GeoRAS GIS tools for support of HEC-RAS using ArcGIS© user's manual version 4.3.93: Davis, Calif., U.S. Army Corps of Engineers, Hydrologic Engineering Center, CPD-83, 244 p.
- Chow, V. T., 1959, Open-channel hydraulics: New York, McGraw-Hill, 680 p.
- Brunner, G. W., 2010, HEC-RAS River Analysis System user's manual, version 4.1: Davis, Calif., U.S. Army Corps of Engineers, Hydrologic Engineering Center, CPD-68, 790 p.
- Cooper, R. M., 2005, Estimation of peak discharges for rural, unregulated streams in western Oregon: U.S. Geological Survey Scientific Investigations Report 2005-5116, 134 p.
- Federal Emergency Management Agency (FEMA), 1999, Flood insurance study for Lane County and incorporated areas: Washington, D.C., 301 p.
- Jin, S., Yang, L., Danielson, P., Homer, C., Fry, J., and Xian, G., 2013, A comprehensive change detection method for updating the National Land Cover Database to circa 2011: Remote Sensing of Environment, v. 132, 159–175.
- Oregon Department of Geology and Mineral Industries (DOGAMI), 2010, McKenzie River lidar data: Lidar Data Quadrangle Series, LDQ-44122B5-Vida.

APPENDIX A: MAP OF HYDRAULIC ANALYSIS RESULTS

Attached to this report is a map depicting the hydraulic analysis results of the 100-year peak discharge for the study reach of Gate Creek.




STATE OF OREGON
DEPARTMENT OF GEOLOGY AND MINERAL INDUSTRIES
www.OregonGeology.org
Brad Avy, Director and State Geologist

BASE FLOOD ELEVATION DETERMINATION REPORT BF-16-01

Lower Reach of Gate Creek,
Lane County, Oregon

By Jed T. Roberts and Matt C. Williams
(See accompanying report.)



APPENDIX B: HYDRAULIC ANALYSIS DATA PACKAGE

Attached to this report is a data package containing the input and output datasets used to perform this study. The data package includes:

- HEC-RAS 4.1 model (HECRAS folder)
- HEC-GeoRAS 10.2 input geometry data in GIS format (HECGeoRAS_Input_Geometry folder)
 - Cross-sections (XSCutLines)
 - Stream centerlines (River)
 - Flowpaths
 - Bridges
- HEC-GeoRAS 10.1 output data in GIS format (HECGeoRAS_Output folder)
 - 100-year flood zone (FloodZone)
 - Model output 100-year flood zone (bp001)
 - 100-year water surface elevation grid (Gate_100yr_WSEL_ft.tif)
 - 100-year depth grid (Gate_100yr_Depth_ft.tif)
 - Cross-sections with computed 100-year water surface elevations (XSCutlines)
- 3-foot resolution lidar DEM in GIS format (Topography folder)
- Hydrologic data table (GateCreek-Hydrology Sheet.xlsx) and supplementary shapefiles (HydroPoint, Subbasin1, Subbasin2)