

015/03E-03DDDD

MT-3331-5

Log on Ground Information

Material	Depth
Fill Gravel	0 - 3 TS
Clay	3 - 6 CC
Sand gravel clay	6 - 10 SG
Sand	10 - 12 SL
Grey clay	12 - 18 CC
Grey clay gravel & boulders	18 - 41 CB
Clay some sand & gravel	41 - 75 258 CC
Cemented gravel some loose layers (mud loss 90-120)	75 - 110 GR
Loose gravel 1" - 1 1/2" ?	110 - 135 GL
Cemented gravel loose layers little clay	135 - 195 GR 198
Shaly clay & gravel	195 - 225 CG 138
Clay	225 - 230 CC
Cement gravel w/clay mixed	230 - 300 102
	GR 25

50065

6711 N. E. 58th Ave. T 1s - R 3e sec. 3
Vancouver, Wash. 98661 Phone: 604-6242

HANSEN DRILLING CO., Inc.

LOG

Name Northwest Pipeline Corp.
Address Site: Gresham Meter Station NE. Hogan
& Division Multnomah County
Date Started 4-30-86 Date Finished 5-3-86

DESCRIPTION:

- (a) Well Depth 300' ft. Diameter 10"
- (b) Depth from ground surface to water level before pumping 0 ft. Bailer tested 0 GPM
- (c) Drawdown of water level is 0 feet.
(pumping level minus static water level)
- (d) Casing - screen - perforation - shoe - etc.
8" surface casing 0 - 18 sch. 40 PVC
6 sks. cement 157 sks. 50# coke
47 sks. Gel (mud) 99
300 ft. 2" sch. 40 PVC
7 Hrs. Mob., demob., clean-up & cement 8" pipe
18 Hrs. Drilling & Chasing
7 Hrs. Anodes, Criculate, coke
20 anodes 75# 100' to 300'
1 1/2" PVC perf. 1/4" hole 1' apart 100'-300'

Hansen Drilling Co., Inc.

PHONE
VANC. 694-6242

6711 N.E. 58TH AVE.
VANCOUVER, WA 98661