



Tsunami Inundation Map Lane-02
Tsunami Inundation Maps for Heceta Head,
Lane County, Oregon
Plate 1

The Oregon Department of Geology and Mineral Industries (DOGAMI) has been identifying and mapping the tsunami inundation hazard along the Oregon coast since 1994. In Oregon, DOGAMI manages the National Tsunami Hazard Mitigation Program, which has been administered by the National Oceanic and Atmospheric Administration (NOAA) since 1995. DOGAMI's work is designed to help cities, counties, and other sites in coastal areas reduce the potential for disastrous tsunami-related consequences by understanding and mitigating this geologic hazard. Using federal funding awarded by NOAA, DOGAMI has developed a new generation of tsunami inundation maps to help residents and visitors along the entire Oregon coast prepare for the next Cascadia Subduction Zone (CSZ) earthquake and tsunami.

The CSZ is the tectonic plate boundary between the North American Plate and the Juan de Fuca Plate (Figure 1). These plates are converging at a rate of about 1.5 inches per year, but the movement is not smooth and continuous. Rather, the plates lock in place, and unreleased energy builds over time. At intervals, this accumulated energy is violently released in the form of a megathrust earthquake rupture, where the North American Plate suddenly slips westward over the Juan de Fuca Plate. This rupture causes a vertical displacement of water that creates a tsunami (Figure 2). Similar rupture processes and tsunamis have occurred elsewhere on the planet where subduction zones exist: for example, offshore Chile in 1950 and 2010, offshore Alaska in 1964, near Sumatra in 2004, and offshore Japan in March 2011.

CSZ Frequency: Comprehensive research of the offshore geologic record indicates that at least 19 major ruptures of the full length of the CSZ have occurred off the Oregon coast over the past 10,000 years (Figure 3). All 19 of these large rupture CSZ events were likely magnitude 8.9 to 9.2 earthquakes (Witter and others, 2011). The most recent CSZ event happened approximately 300 years ago on January 26, 1700. Sand deposits carried offshore and left by the 1700 event have been found 12 miles inland; other tsunami sand deposits have also been discovered in estuaries 6 miles inland. As shown in Figure 3, the range in time between these 19 events varies from 110 to 1,150 years, with a median time interval of 490 years. In 2008 the United States Geological Survey (USGS) released the results of a study announcing that the probability of a magnitude 8-9 CSZ earthquake occurring over the next 30 years is 10% and that such earthquakes occur about every 500 years (WGCEP, 2008).

CSZ Model Specifications: The sizes of the earthquake and its resultant tsunami are primarily driven by the amount and geometry of the slip that takes place when the North American Plate snags westward over the Juan de Fuca Plate during a CSZ event. DOGAMI has modeled a wide range of earthquake and tsunami sizes that take into account different fault geometries that could simplify the amount of seafloor displacement and increase tsunami inundation. Seismic geophysical profiles show that there may be a steep play fault running nearly parallel to the CSZ but closer to the Oregon coastline (Figure 2). The effect of this slip fault moving during a full-rupture CSZ event would be an increase in the amount of vertical displacement of the Pacific Ocean, resulting in an increase of the tsunami inundation onshore in

A diagram showing the Juan de Fuca Plate, a small tectonic plate located off the west coast of North America. The plate is shown moving northward, indicated by an arrow. It is bounded by the Pacific Plate to the west and the North American Plate to the east. The Juan de Fuca Ridge is shown as a mid-ocean ridge where the plate is formed. The Cascadia Subduction Zone is shown as a trench where the plate is being subducted under the North American Plate. The diagram also shows the British Columbia coast and the Washington coast. The Juan de Fuca Plate is labeled as being 100 miles wide and 100 miles long. The diagram is credited to the University of Washington.

Figure 1: This block diagram depicts the tectonic setting of the region. See Figure 2 for the sequence of events that occur during a Cascadia Subduction Zone megathrust earthquake and tsunami.

Figure 2: The North American Plate rides over the descending Juan de Fuca Plate at a rate of approximately 3.5 inches per year.

A The North American Plate moves over the Juan de Fuca Plate. The Juan de Fuca Plate is shown descending into the mantle. The North American Plate is shown moving over it. The rate of movement is approximately 3.5 inches per year.

B Because the two plates are stuck in place at the "locked zone," strain builds up over time and the North American Plate bulges up.

C Eventually the locked zone ruptures and causes a great earthquake. The sudden slip of the two plates displace Pacific Ocean water upward and creates a tsunami.

D Displaced and uplifted Pacific Ocean water rushes in all directions.

E Along the Oregon coast, tsunami waves run up onto the beach for several hours.




Figure 3: This chart depicts the timing, frequency, and magnitude of the last 19 great Cascadia Subduction Zone events over the past 10,000 years. The most recent event occurred on January 26, 1700. The 1700 event is considered to be a "medium sized" event. The data used to create this chart came from research that examined the many submarine landslides, known as "turbidites," that are triggered only by these great earthquakes (Witter and others, 2011). The loose correlation is "the bigger the turbidite, the bigger the earthquake."

		Entire Map Area		Unincorporated Areas	
Total Buildings		43		43	
Buildings within Tsunami Zones*					
Small		0		0	
Medium		1		1	
Large		2		2	
Extra Large		5		5	
Extra Extra Large		7		7	
Percent of Buildings within Tsunami Zones					
Small		0.0%		0.0%	
Medium		2.3%		2.3%	
Large		4.7%		4.7%	
Extra Large		11.6%		11.6%	
Extra Extra Large		16.3%		16.3%	

*Building counts shown are based on polygon centroids and are cumulative within the map area




Figure 4: The table and chart show the number of buildings inundated for each "tsunami T-shirt scenario" for cities and unincorporated portions of the map.

Figure 5: This chart depicts the tsunami waves as they arrive at the selected reference point (simulated gauge station). It shows the change in wave heights for all five tsunami scenarios over an 1-hour period. The starting wave elevation (0.0-hour) takes into account the local land subsidence or uplift caused by the earthquake. Wave heights vary through time, and the first wave will not necessarily be the largest as waves interfere and reflect off local topography and bathymetry. Any absence of data indicates periods for which tsunami inundation has not yet reached or has receded from the station location and dry land is exposed.

Figure 6: These profiles depict the expected maximum tsunami wave elevation for the five "tsunami T-shirt scenarios" along lines A-A' and B-B'. The tsunami scenarios are modeled to occur at high tide and to account for local subsidence or uplift of the ground surface.


Oregon DOWAMI has also incorporated physical evidence that suggests that portions of the coast may drop 4 to 10 feet during the earthquake; this effect is known as subsidence. Detailed information on fault geometries, subsidence, computer models, and the methodology used to create the tsunami scenarios presented on this map can be found in DOWAMI Special Papers 41 (Priest and others, 2009) and 43 (Witter and others, 2011).

This tsunami inundation map displays the output of computer models representing five selected tsunami scenarios, all of which include the earthquake-produced subsidence and the tsunami-amplifying effects of the play fault. Each scenario assumes that a tsunami occurs at Mauna Higher High Water (MHHW) tide; MHHW is defined as the average height of the higher high tides observed over an 18-year period at the Yaguana Bay (Central Coast Model) tide gauge. To make it easier to understand this scientific material and to enhance the educational aspects of hazard mitigation and response, the five scenarios are labeled as 'T-shirt sizes' ranging from Small, Medium, Large, Extra Large, to Extra Extra Large (S, M, L, XL, XXL). The map legend depicts the respective amounts of slip, the frequency of occurrence, and the earthquake magnitude for these five scenarios. Figure 4 shows the cumulative number of buildings inundated within the map area.

The computer simulation model output is provided to DOGAMI as millions of points with values that indicate whether the location of each point is wet or dry. These points are converted to wet and dry contour lines that form the extent of inundation. The transition area between the wet and dry contour lines is termed the Wet/Dry Zone, which equates to the amount of error in the model when determining the maximum inundation for each scenario. Only the XXL Wet/Dry Zone is shown on this map.

This map also shows the regulatory tsunami inundation line (Oregon Revised Statutes 455.446 and 455.447), commonly known as the Senate Bill 379 line. Senate Bill 379 (1995) instructed DOGAMI to establish the area of expected tsunami inundation based on scientific evidence and tsunami modeling in order to prohibit the construction of new essential and special occupancy structures in this tsunami inundation zone (Priest, 1995).

Time Series Graphs and Wave Elevation Profiles: In addition to the tsunami scenarios, the computer model produces time series data for "gauge" locations in the area. These points are simulated gauge stations that record the time, in seconds, of the tsunami wave arrival and the wave height observed. It is especially noteworthy that the greatest wave height and velocity observed are not necessarily associated with the first tsunami wave to arrive onshore. Therefore evacuees should not assume that the tsunami event is over until the proper authorities have sounded the all-clear signal at the end of the evacuation. Figure 5 depicts the tsunami waves as they arrive at a simulated gauge station. Figure 6 depicts the overall wave height and inundation extent for all five scenarios at the profile locations shown on this map.



Earthquake Size	Average Slip Range (ft)	Maximum Slip Range (ft)	Time to Accumulate Slip (yrs)	Earthquake Magnitude
XXL	59 to 72	118 to 144	1,200	-9.1
XL	56 to 72	115 to 144	1,050 to 1,200	-9.1
L	36 to 49	72 to 98	650 to 800	-9.0
M	23 to 30	46 to 62	425 to 525	-8.9
S	13 to 16	30 to 36	300	-8.7
	XXL Wet/Dry Zone			

	Urban Growth Boundary		Fire Station
	Building Footprint		Police Station
	Simulated Gauge Station		School
	Profile Location		Hospital/Urgent Care Clinic
	Senate Bill 379 Line		U.S. Highway
	State Park		State Highway
	Elevation Contour (25 ft intervals up to 200 ft)		Improved Road

The map displays the Willamette River with 10 sampling locations marked by numbered boxes. The river flows from the north (top) to the south (bottom). Locations 01 through 06 are situated in the upper reaches of the river, while locations 07 through 10 are in the lower reaches. The river is bordered by green areas representing land. A locator map of Oregon is shown to the right, with a black dot indicating the location of the study area in the western part of the state. Labels for 'Lincoln Lane', 'Benton', 'Large Douglas', and 'Siltcoos Lake' are present. A legend at the bottom identifies the locations by name and lane number.

Lane-01	Neptune	Lane-05	Cushman - Wendson
Lane-02	Becca Head	Lane-06	Tiernan - Mapleton
Lane-03	Morris Lake	Lane-07	Dunes City
Lane-04	Florence	Lane-08	Siltcoos Lake

Source Data: This map is based on hydrodynamic tsunami modeling by Zhang Jieping and his colleagues at Oregon University Portland, Oregon. Model data inputs were created by John T. English and George E. Priest, Department of Geology and Mineral Industries (DOGAMI), Portland, Oregon.

Hydrology data: Portcove, critical facilities, and building footprints were derived from the Oregon Department of Transportation (ODOT) by Robert L. Smith and Sean G. Pankratz, DOGAMI, in 2013 (GIS file set by Robert L. Smith).

2012 growth boundaries: 2012 were provided by the Oregon Department of Land Use and Conservation and Development (DLUD).

Topographic data: 2012 provided by Lane County were edited by DOGAMI to improve the spatial accuracy of the features or to add newly constructed roads not present in the original data files.

LiDAR data: Data from DOGAMI Lidar Data Quadrangles LQ2011-44124a, LQ2011-44124b, LQ2011-44124c, LQ2011-44124d, LQ2011-44124e, LQ2011-44124f, LQ2011-44124g, LQ2011-44124h, LQ2011-44124i, LQ2011-44124j, LQ2011-44124k, LQ2011-44124l, LQ2011-44124m, LQ2011-44124n, LQ2011-44124o, LQ2011-44124p, LQ2011-44124q, LQ2011-44124r, LQ2011-44124s, LQ2011-44124t, LQ2011-44124u, LQ2011-44124v, LQ2011-44124w, LQ2011-44124x, LQ2011-44124y, LQ2011-44124z, LQ2011-44125a, LQ2011-44125b, LQ2011-44125c, LQ2011-44125d, LQ2011-44125e, LQ2011-44125f, LQ2011-44125g, LQ2011-44125h, LQ2011-44125i, LQ2011-44125j, LQ2011-44125k, LQ2011-44125l, LQ2011-44125m, LQ2011-44125n, LQ2011-44125o, LQ2011-44125p, LQ2011-44125q, LQ2011-44125r, LQ2011-44125s, LQ2011-44125t, LQ2011-44125u, LQ2011-44125v, LQ2011-44125w, LQ2011-44125x, LQ2011-44125y, LQ2011-44125z, LQ2011-44126a, LQ2011-44126b, LQ2011-44126c, LQ2011-44126d, LQ2011-44126e, LQ2011-44126f, LQ2011-44126g, LQ2011-44126h, LQ2011-44126i, LQ2011-44126j, LQ2011-44126k, LQ2011-44126l, LQ2011-44126m, LQ2011-44126n, LQ2011-44126o, LQ2011-44126p, LQ2011-44126q, LQ2011-44126r, LQ2011-44126s, LQ2011-44126t, LQ2011-44126u, LQ2011-44126v, LQ2011-44126w, LQ2011-44126x, LQ2011-44126y, LQ2011-44126z, LQ2011-44127a, LQ2011-44127b, LQ2011-44127c, LQ2011-44127d, LQ2011-44127e, LQ2011-44127f, LQ2011-44127g, LQ2011-44127h, LQ2011-44127i, LQ2011-44127j, LQ2011-44127k, LQ2011-44127l, LQ2011-44127m, LQ2011-44127n, LQ2011-44127o, LQ2011-44127p, LQ2011-44127q, LQ2011-44127r, LQ2011-44127s, LQ2011-44127t, LQ2011-44127u, LQ2011-44127v, LQ2011-44127w, LQ2011-44127x, LQ2011-44127y, LQ2011-44127z, LQ2011-44128a, LQ2011-44128b, LQ2011-44128c, LQ2011-44128d, LQ2011-44128e, LQ2011-44128f, LQ2011-44128g, LQ2011-44128h, LQ2011-44128i, LQ2011-44128j, LQ2011-44128k, LQ2011-44128l, LQ2011-44128m, LQ2011-44128n, LQ2011-44128o, LQ2011-44128p, LQ2011-44128q, LQ2011-44128r, LQ2011-44128s, LQ2011-44128t, LQ2011-44128u, LQ2011-44128v, LQ2011-44128w, LQ2011-44128x, LQ2011-44128y, LQ2011-44128z, LQ2011-44129a, LQ2011-44129b, LQ2011-44129c, LQ2011-44129d, LQ2011-44129e, LQ2011-44129f, LQ2011-44129g, LQ2011-44129h, LQ2011-44129i, LQ2011-44129j, LQ2011-44129k, LQ2011-44129l, LQ2011-44129m, LQ2011-44129n, LQ2011-44129o, LQ2011-44129p, LQ2011-44129q, LQ2011-44129r, LQ2011-44129s, LQ2011-44129t, LQ2011-44129u, LQ2011-44129v, LQ2011-44129w, LQ2011-44129x, LQ2011-44129y, LQ2011-44129z, LQ2011-44130a, LQ2011-44130b, LQ2011-44130c, LQ2011-44130d, LQ2011-44130e, LQ2011-44130f, LQ2011-44130g, LQ2011-44130h, LQ2011-44130i, LQ2011-44130j, LQ2011-44130k, LQ2011-44130l, LQ2011-44130m, LQ2011-44130n, LQ2011-44130o, LQ2011-44130p, LQ2011-44130q, LQ2011-44130r, LQ2011-44130s, LQ2011-44130t, LQ2011-44130u, LQ2011-44130v, LQ2011-44130w, LQ2011-44130x, LQ2011-44130y, LQ2011-44130z, LQ2011-44131a, LQ2011-44131b, LQ2011-44131c, LQ2011-44131d, LQ2011-44131e, LQ2011-44131f, LQ2011-44131g, LQ2011-44131h, LQ2011-44131i, LQ2011-44131j, LQ2011-44131k, LQ2011-44131l, LQ2011-44131m, LQ2011-44131n, LQ2011-44131o, LQ2011-44131p, LQ2011-44131q, LQ2011-44131r, LQ2011-44131s, LQ2011-44131t, LQ2011-44131u, LQ2011-44131v, LQ2011-44131w, LQ2011-44131x, LQ2011-44131y, LQ2011-44131z, LQ2011-44132a, LQ2011-44132b, LQ2011-44132c, LQ2011-44132d, LQ2011-44132e, LQ2011-44132f, LQ2011-44132g, LQ2011-44132h, LQ2011-44132i, LQ2011-44132j, LQ2011-44132k, LQ2011-44132l, LQ2011-44132m, LQ2011-44132n, LQ2011-44132o, LQ2011-44132p, LQ2011-44132q, LQ2011-44132r, LQ2011-44132s, LQ2011-44132t, LQ2011-44132u, LQ2011-44132v, LQ2011-44132w, LQ2011-44132x, LQ2011-44132y, LQ2011-44132z, LQ2011-44133a, LQ2011-44133b, LQ2011-44133c, LQ2011-44133d, LQ2011-44133e, LQ2011-44133f, LQ2011-44133g, LQ2011-44133h, LQ2011-44133i, LQ2011-44133j, LQ2011-44133k, LQ2011-44133l, LQ2011-44133m, LQ2011-44133n, LQ2011-44133o, LQ2011-44133p, LQ2011-44133q, LQ2011-44133r, LQ2011-44133s, LQ2011-44133t, LQ2011-44133u, LQ2011-44133v, LQ2011-44133w, LQ2011-44133x, LQ2011-44133y, LQ2011-44133z, LQ2011-44134a, LQ2011-44134b, LQ2011-44134c, LQ2011-44134d, LQ2011-44134e, LQ2011-44134f, LQ2011-44134g, LQ2011-44134h, LQ2011-44134i, LQ2011-44134j, LQ2011-44134k, LQ2011-44134l, LQ2011-44134m, LQ2011-44134n, LQ2011-44134o, LQ2

References:
2007 Working Group on California Earthquake Probabilities (WGCEP 2008). The Uniform California Earthquake Rupture Forecast, Version 2 (UCERF 2): U.S. Geological Survey Open-File Report 2007-1437 and California Geological Survey Special Report 203 (<http://pubs.usgs.gov/of/2007/1437/>).

Priest, G.R. 1995. Explanation of mapping methods and use of the tsunami hazard maps of the Oregon coast. Oregon Department of Geology and Mineral Industries Open-File Report O-95-67. 96 p.

Priest, G.R., Goldfinger, C., Wang, K., Witter, R.C., Zhang, Y., and Baptit AM. 2009. Tsunami hazard assessment of the northern Oregon coast: multi-deterministic approach tested at Cannon Beach, Clatsop County, Oregon. Oregon Department of Geology and Mineral Industries Special Report 41. 87 p.

Witter, R.C., Zhang, Y., Wang, K., Priest, G.R., Goldfinger, C., Stimey, L., English, T.J., and Ferro, P.A. 2011. Simulating tsunami inundation at Bandon, Coos County, Oregon, using hypothetical Cascadia and Ale

Witter, R.C., Zhang, Y., Wang, K., Priest, G.R., Goldfinger, C., Stirmely, L., English, J.T., and Ferro, P.A., 2011, Simulating tsunami inundation at Bandon, Coos County, Oregon, using hypothetical Cascadia and Alsea earthquake scenarios; Oregon Department of Geology and Mineral

Industries Special Paper 43, 57 p.


Software: Esri ArcGIS® 10.1, Microsoft® Excel®, and Adobe® Illustrator®

Funding: This map was funded under award #NA09NWS467001 the National Oceanic and Atmospheric Administration (NOAA) through the National Tsunami Hazard Mitigation Program.

Map Data Creation/Development:
Tsunami Inundation Scenarios: George R. Priest, Laura L. Stimpely,
E. Coe, Paul A. Ferro, Sean G. Pickner, Rachel L. Smith
Basemap Data: Kaleena L.B. Hughes, Sean G. Pickner

Map Production:
Cartography: Kaleena L.B. Hughes, Sean G. Pickner,
Taylore E. Wille
Text: Don W.T. Lewis, Rachel L. Smith
Editing: Don W.T. Lewis, Rachel L. Smith
Publication: Deborah A. Schueller
Map Date: 02/28/2013

Publication: Deborah A. Schuller
Map Date: 02/28/2013



For copies of this publication contact:
Nature of the Northwest Information Center
800 NE Oregon Street, #28, Ste. 565
Portland, Oregon 97232
telephone (971) 673-2331
<http://www.naturenw.org>