



The Oregon Department of Geology and Mineral Industries (DOGAMI) has been identifying and mapping the tsunami inundation hazard along the Oregon coast since 1994. In Oregon, DOGAMI manages the National Tsunami Hazard Mitigation Program, which has been administered by the National Oceanic and Atmospheric Administration (NOAA) since 1995. DOGAMI's work is designed to help cities, counties, and other sites in coastal areas reduce the potential for disastrous tsunami-related consequences by understanding and mitigating this geologic hazard. Using federal funding awarded by NOAA, DOGAMI has developed a new generation of tsunami inundation maps to help residents and visitors along the entire Oregon coast prepare for the next Cascadia Subduction Zone (CSZ) earthquake and tsunami, as well as for far-travelled, or "distant" tsunamis.

The 'Ring of Fire' is also called the Circum-Pacific Belt, is the zone of earthquake activity surrounding the Pacific Ocean. It is an arc stretching from New Zealand, along the eastern edge of Asia, north across the Aleutian Islands of Alaska, and south along the coast of North and South America (Figure 1). The Ring of Fire is located at the borders of the Pacific Plate and other major tectonic plates. The Pacific Plate is colliding with and sliding underneath other plates creating subduction zones that eventually release energy in the form of an earthquake rupture. This rupture causes a vertical displacement of water that creates a tsunami. When these events occur around the Ring of Fire but not directly off the Oregon coast, they take more time to travel the Pacific Ocean and arrive onshore in Oregon (Figure 2). Distant earthquake/tsunami events have affected the Oregon coast: for example, offshore Alaska in 1964 and offshore Japan in March 2011.

Historically, about 28 distant tsunamis have been documented by Oregon tide gauges since 1854. The most severe was generated by the 1964 M9.2 Prince William Sound earthquake in Alaska. Oregon was hit hard by the tsunami, which killed four people and caused an estimated 750,000 to 1 million dollars in damage to bridges, houses, cars, boats, and sea walls. The greatest tsunami damage in Oregon did not occur along the ocean front as one might expect, but in the estuary channels located further inland. Of the communities affected, Seaside was inundated by a 10 foot tsunami wave and was the hardest hit. Tsunami wave heights reached 10 to 115 feet in the Nehalem River, 10 to 115 feet at Depoe Bay, 115 feet at Newport, 10 to 11 feet at Florence, 11 feet at Reedsport, 11 feet at Brookings, and 14 feet at Coos Bay (Witter and others, 2011).

Alaska-Aleutian Model Specifications: DOGAMI model two distant tsunamigenic and tsunami scenarios involving M9.2 earthquakes originating near the Gulf of Alaska. The first scenario attempts to replicate the 1964 Prince William Sound event, and the second scenario represents a hypothetical maximum event. This maximum event is the same model used by the U.S. Geological Survey (USGS) in their 2006 tsunami hazard assessment of Seaside (TPSW, 2006). This model uses extreme fault model parameters that result in maximum seafloor uplift nearly twice as large as in the 1964 earthquake. The selected source for the Aleutian chain of islands also has higher energy release directed toward the Oregon coast than other Aleutian source locations. For these reasons the hypothetical "Alaska Maximum" scenario is selected as the worst case distant tsunami scenario for Oregon. Detailed information on fault geometries, subsidence, computer models, and the methodology used to create the tsunami scenarios presented on this map can be found in DOGAMI Special Paper 43 (Witter and others, 2011).

A world map showing the boundaries of the major tectonic plates. The plates are labeled: North America, South America, Eurasia, Africa, Australia, Antarctic, Pacific, Indian, and others. The boundaries are marked with red lines, and some are labeled with 'divergent' and 'convergent'.

Figure 2. The "Ring of Fire" is a zone of active earthquakes and volcanoes that rings much of the Pacific Ocean, including the Oregon coast. Volcanoes and earthquakes on this ring are caused by the movements of tectonic plates. One type of movement is called subduction — when thin, oceanic plates, such as those that compose the rock beneath the Pacific Ocean, sink beneath thicker, lighter plates that make up continental plates. Earthquakes that occur as a result of subduction can trigger tsunamis.

Figure 2: This image depicts the actual initial tsunami arrival times, in hours, around the Pacific Rim from the 1964 Prince William Sound earthquake. This magnitude 9.2 earthquake and resulting tsunami caused 125 deaths and \$311 million in property loss, \$84 million and 106 deaths in Alaska (NGDC/WDC). The tsunami devastated many towns along the Gulf of Alaska, left serious damage in British Columbia, Hawaii, and along the west coast of the United States, and was recorded on tide gauges in Cuba and Puerto Rico.

	Entire Map		Unincorporated
	Area	Florence	Areas
Total Buildings	650	16	634
Buildings within Tsunami Zones*			
Alaska M9.2 (1964)		0	0
Alaska Maximum		9	3
Percent of Buildings within Tsunami Zones			
Alaska M9.2 (1964)		0.0%	0.0%
Alaska Maximum		1.4%	0.5%

*Building counts shown are based on polygon centroids and are cumulative within the map area




Figure 3: The table and chart show the number of buildings inundated for the Alaska M9.2 (1964) and the Alaska Maximum tsunami scenarios for cities and unincorporated portions of the map.


This tsunami inundation map displays the output of computer models representing the two selected tsunami scenarios: Alaska M9.2 (1964) and the Alaska Maximum. All tsunami simulations were run assuming that prevailing tide was static (no flow) and equal to Mean Higher High Water (MHHW) tide; MHHW is defined as the average height of the higher high tides observed over an 18-year period at the Yaquina Bay (Central Coast) tide gauge. The map legend depicts the respective amounts of deformation and the earthquake magnitude for these two scenarios. Figure 3 shows the cumulative number of buildings inundated within the map area.

The computer simulation model output is provided to DOGAMI as millions of points with values that indicate whether the location of each point is wet or dry. These points are converted to wet and dry contour lines that form the extent of inundation. The transition area between the wet and dry contour lines is termed the Wet/Dry Zone, which equates to the amount of error in the model when determining the maximum inundation for each scenario. Only the Alaska Maximum Wet/Dry Zone is shown on this map.

This map also shows the regulatory tsunami inundation line (Oregon Revised Statutes 455.446 and 455.447), commonly known as the Senate Bill 379 line. Senate Bill 379 (1995) instructed DOGAMI to establish the area of expected tsunami inundation based on scientific evidence and tsunami modeling in order to prohibit the construction of new essential and special occupancy structures in this tsunami inundation zone (Priest, 1995).

Time Series Graphs and Wave Elevation Profiles: In addition to the tsunami scenarios, the computer model produces time series data for "gauge" locations in the area. These points are simulated gauge stations that record the time, in seconds, of the tsunami wave arrival and the wave height observed. It is especially noteworthy that the greatest wave height and velocity observed are not necessarily associated with the first tsunami wave to arrive onshore. Therefore evacuees should not assume that the tsunami event is over until the proper authorities have sounded the all-clear at the end of the evacuation. Figure 4 depicts the tsunami waves as they arrive at a simulated gauge station. Figure 5 depicts the overall wave height and inundation extent for the two scenarios at the profile locations shown on this map.

2013



Maximum Wave Elevation Profiles




Figure 5: These profiles depict the expected maximum tsunami wave elevation for the two Alaska tsunami scenarios along lines A-A' and B-B'. The tsunami scenarios are modeled to occur at a static (no flow) tide and equal to the Mean Higher High Water (MHHW) high tide.

Figure 1 is a map of the study area. It shows the Gulf of Mexico to the north and east of the study area. The study area is located in the Gulf of Mexico, and its location is indicated by a red dot. The map includes a scale bar showing distances in miles (0, 0.25, 0.5) and kilometers (0, 0.25, 0.5). A north arrow is also present.

Earthquake Size	Slip / Deformation	Earthquake Magnitude
	Alaska M9.2 (1964)	~9.2
	Alaska Maximum Vertical seafloor deformation estimate Uniform slip on 12 subfaults with each assigned values ranging from 49 to 99 feet.	~9.2
	Alaska Maximum Wet/Dry Zone	
	Urban Growth Boundary	Fire Station
	Building Footprint	Police Station
	Simulated Gauge Station	School
	Profile Location	Hospital / Urgent Care Clinic
	Senate Bill 379 Line	U.S. Highway
	State Park	State Highway
	Elevation Contour (25 ft intervals up to 200 ft)	Improved Road

The map displays the Willamette Valley region in Oregon, with the eight study watersheds highlighted in black and numbered 01 through 08. The watersheds are located in the following order from north to south: 01 (Neptune), 02 (Heceta Head), 03 (Mercur Lake), 04 (Cushman), 05 (Wendson), 06 (Terran), 07 (Magelston), and 08 (Burns City). The map also shows major roads (I-5, I-205, I-405) and cities (Portland, Salem, Eugene). An inset map shows the location of the study area within the state of Oregon.

Watershed Number	Watershed Name
01	Neptune
02	Heceta Head
03	Mercur Lake
04	Cushman
05	Wendson
06	Terran
07	Magelston
08	Burns City

Source Data
This study is based on hydrodynamic tsunami modeling by Joseph Zhang, Oregon Health and Science University, Portland, Oregon. Model data input were created by John H. Hinkle, Oregon Department of Geology and Mineral Industries (DOGAMI), Portland, Oregon.
Hydrology data, contours, critical facilities, and building footprints were created by DOGAMI. Senate Bill 379 line data were redigitized by Rachel L. Smith and Sean S. Pickner, DOGAMI, in 2011 (GIS file set in press, 2012).
Urban growth boundaries (2011) were provided by the Oregon Department of Land Conservation and Development (OLCD).
Transportation data (2010) provided by Lane County were used to improve the spatial accuracy of the features or to add newly constructed roads not present in the original data layer.
Lidar data are from DOGAMI Lidar Data Quadrangles (LQD_2011-4412-A to -M; Merger Line and LQD_2011-4412-A to -M).

Source Data:
This map is based on hydrodynamic tsunami modeling by Joseph Zhang, Oregon Health and Science University, Portland, Oregon. Model data input were created by John T. English and George R. Priest, Department of Geology

Hydrology data, contours, critical facilities, and building footprints were created by DOGAMI. Senate Bill 379 line data were redigitized by Rachel L. Smith and Sean G.

Transportation data (2010) provided by Lane County were edited by DOGAMI to improve the spatial accuracy of the features or to add newly constructed roads not

Lidar data are from DOGAMI Lidar Data Quadrangles LDQ-2011-44124-A1-Merced Lake and LDQ-2011-44124-A1-4 (see http://www.dogami.com/publications/lidar_data).

Coordinate System: Oregon Statewide Lambert
Conformal Conic, Unit: International Feet, Horizontal
Datum: NAD 1983 HARN, Vertical Datum: NAVD 1988.
Graticule shown with geographic coordinates
(latitude / longitude).

Funding: This map was funded under award #N059NW54670014 by the National Oceanic and Atmospheric Administration (NOAA) through the National Tsunami Hazard Mitigation Program.

Basemap Data: Kaleena L.B. Hughes, Sean G. Pickner

Map Production:
Cartography: Kaleena L.B. Hughes, Sean G. Pickner,
Taylor E. Wille
Data: Greg M.H. Lewis, Deborah L. Smith

Publication: Deborah A. Schueller
Map Date: 02/28/2013

Tsunami Inundation Map Lane-03

Tsunami Inundation Maps for Mercer Lake,
Lane County, Oregon

Plate 2